



### PRODUCT SPECIFICATIONS

---

Size	7" x 48"
Thickness	2 mm 12-mil
Wear Layer	ArmourGuard Microbead Technology No
Finish	Light Commercial
Micro Beveled Edge	Direct Glue
Traffic Use	SAR 5000 (Pressure Sensitive Adhesive)
Installation	14
Recommended Adhesive	32.7
Pieces Per Carton	85
SF Per Carton	2,779.50
Cartons Per Pallet	100% Virgin
SF Per Pallet	
Material	

### WARRANTY

---

7 Year Commercial / 10 Year Residential

### PERFORMANCE

---

	Pass As specified 0.016 in / lin ft
	Pass As specified 0.005 in / lin ft
ASTM F2055 Size and Tolerance	Pass Maximum 0.010 in
ASTM F386 Thickness	Pass Average < 8%
ASTM F2055 Squareness	Passes 6mm mandrel / no crack or break
ASTM F1914 Residual Indentation	Pass 0.011 in / ft < 0.020 in / ft
ASTM F137 Flexibility	Pass No change / slight change
ASTM F2199 Dimensional Stability	Pass < 8 (delta E) average
ASTM F925 Chemical Resistance	Pass < 8 (delta E) average
ASTM F1514 Resistance to Heat	Class 1 (< 0.45 w/cm2)
ASTM F1515 Resistance to Light	Passes <450
ASTM E648 Critical Radiant Flux	Pass ADA Compliant (> 0.50)
ASTM E662 Optical Smoke Density	Pass 1000 psi / 250 psi (< 0.005 in)
ASTM C1028 Slip Resistance	
ASTM F970 Static Load	

