SOUNDSTOP ACOUSTICAL GLUE DOWN LVT

3MM PRODUCT DATA SHEET | ACOUSTICAL GLUE DOWN LVT WITH ATTACHED SOUNDPAD

Advanced Flooring Concepts
Leaders in Innovative Commercial Flooring!

PRODUCT SPECIFICATIONS

Product Type	Soundstop Acoustical Glue Down LVT
Size	7" × 48" · 9" × 48"
Thickness	3.0 mm
Wear Layer	6-mil · 8-mil · 12-mil
Pad	1mm Soundpad Attached
Surface Finish	DiamondGuard™ / HealthGuard™
Installation	Direct Glue Down
Recommended Adhesive	SAR 5000 (Pressure Sensitive)
Material	100% Virgin LVT

PACKAGING & LOGISTICS

SF Per Carton	48 s.f.
Boxes Per Pallet	48
SF Per Pallet	2,883 s.f.
Pallets Per Truckload	20

ACOUSTIC PERFORMANCE

3/4" GYPSUM UNDERLAYMENT, 18" OPEN WEB TRUSS,
TESTED WITHOUT A SOUNDMAT

61	56	68
STC RATING	IIC RATING	HIIC RATING

COMPLIANCE STANDARDS

ISO 24342:2018	Determination of Residual Indentation
ISO 24346:2006	Determination of Flexibility
ISO 23997:2007	Determination of Mass per Unit Area
ISO 23999:2021	Determination of Dimensional Stability
ISO 4918:2016	Castor Chair Test
ISO 105-B02:2014	Light Fastness
ASTM F1515-21	Resistance to Light
EN ISO 10582:2018	Heterogeneous PVC Floor Coverings
EN 16094:2021	Micro-Scratch Resistance